

	TEM	QTY	DESCRIPTION
ı	1	1 EA	" EPOXY COATED TAPPING SADDLE (" O.D. x " FLG) OR" FABRICATED TAPPING SADDLE (" O.D. x " FLG) OR" FABRICATED WELD NOZZLE (" O.D. x " FLG)" STAINLESS STEEL TAPPING SADDLE
(2	1 EA	" FLG GATE VALVE PER SBMWD STD. DWG. W3.1
(3	1 EA	" TEST PLATE
(4	1 EA	" FLANGE x MJ ADAPTER (RESTRAIN WITH "MEGALUG" RESTRAINT)
(5	LF	" CLASS 350 DUCTILE IRON PIPE (RESTRAINED W/ "MEGALUG" RESTRAINT OR APPROVED EQUAL)
(6	1 EA	" PIPELINE SEAL AND INSULATOR, INC INSULATING KIT TO BE USED BETWEEN THE TAPPING SADDLE AND VALVE WHEN DISSIMILAR METALS (DUCTILE IRON AND STEEL) ARE INVOLVED
(7	1 EA	2" CHLORINATION AND FLUSHING PORT PER SBMWD STD. DWG. W6.7 (INSTALL WHEN LATERAL IS LONGER THAN 10')

REVISION DATE: 2/1/2011

		SAN BER	NARDINO MUNICIPAL	WATER DEPARTMENT	DRAWING NUMBER	
		TADDING	DETAIL FOR	AU AND LABOE		
G.S.B.	FEB 11		_	4" AND LARGER	SBMWD	
D.D.M.	D.D.M. SEPT 09 CONTRACTOR-INSTALLED MAINS					
REVISION	DATE		Or A		W3.5A	
scale: NONE		APPROVED _	WARREN HUANG, P.E. RCE 49208	DATE07/04/2019	-	