



ITEM	QTY	DESCRIPTION
1	1 EA	" EPOXY COATED TAPPING SADDLE (" O.D. x " FLG) OR " FABRICATED TAPPING SADDLE (" O.D. x " FLG) OR " FABRICATED WELD NOZZLE (" O.D. x " FLG) " STAINLESS STEEL TAPPING SADDLE
2	1 EA	" FLG X MJ GATE VALVE PER SBMWD STD. DWG. W3.1
3	1 EA	END CAP WITH 2" FLUSH PORT (FLUSH PORT PER SBMWD STD. DWG. W6.7) (RESTRAINED)
4	1 EA	MJ SLEEVE (RESTRAINED W/ "MEGALUG" RESTRAINT)
(5)	LF	" CLASS 350 DUCTILE IRON PIPE (RESTRAINED W/ "MEGALUG" RESTRAINT OR APPROVED EQUAL)
6	1 EA	" PIPELINE SEAL AND INSULATOR, INC INSULATING KIT TO BE USED BETWEEN THE TAPPING SADDLE AND VALVE WHEN DISSIMILAR METALS (DUCTILE IRON AND STEEL) ARE INVOLVED

REVISION DATE: 1/3/2011

D.D.M.	JAN. 11	SAN BERN	NARDINO MUNICIPAL \	WATER DEPARTMENT	DRAWING NUMBER	
C.L.R.	APRIL 08					
C.L.R.	SEPT. 07	TAPPING	R SBMWD			
M.H.L.	DEVELOPER-INSTALLED MAINS					
REVISION	DATE	A DDD OVED	Mad	DATE 07/04/2010	→ W3.5	
SCALE: N	IONE	APPROVED _	WARREN HUANG, P.E. RCE 49208	DATE07/04/2019	-	